



Moulded Flexible Racks

Materials

0.8-2.0 MOD

20° P.A.

STD : Duracon
overall length: 2000mm



Moulded Duracon racking can be used with various spur gears. The racking can be mounted directly onto the application surface by using an aluminium fixing rail which the racking slides into. Available in 2 metre lengths and can be easily cut to the application requirements. The aluminium fixing rail is sold in 1 metre lengths and a **FIXING KIT** containing retaining clips and screws is also available as listed below.

DISCOUNTS



1 - 4	List Price
5 - 9	- 5%
10 - 19	- 10%

PART NUMBER	MOD	A	B	C	D	E	F	G	Allowable Force For Bending (Kg)	(N)	PRICE EACH
DR0.8-2000	0.8	8	3.7	3	3.8	1.5	1.80	0.7	11.40	111.8	£51.79
DR1-2000	1.0	10	4.9	4	5.0	2	2.25	0.9	16.41	160.9	£70.23
DR1.5-2000	1.5	12	8.0	5	6.5	2.3	3.38	1.0	16.46	161.4	£85.58
DR2-2000	2.0	15	10.1	6	8.0	2.5	4.50	1.1	27.01	264.9	£97.41

Rack Fixings

Materials

STD : Aluminium A6063S



PART NUMBER	Dimensions for Screw Fixings					To Suit Rack	PRICE PER PACK OF 10
	A	B	C	D	E		
SRS1	10.2	8	4.5	2.7	1.2	DR0.8 and DR1.0	£17.36
SRS2	11.4	8	5.6	3.9	1.4	DR1.5 and DR2.0	£17.36

Various aluminium fixings specifically for the Moulded Flexible Racks as described above.

PART NUMBER	Dimensions for Rail Fixings					PRICE EACH
	A	B	C	D	E	
ARL-0.8	10.3	4.4	4.7	2.0	1.7	£17.09
ARL-1.0	12.3	5.6	5.2	2.0	2.2	£19.29
ARL-1.5	14.3	7.2	5.5	2.0	2.5	£22.98
ARL-2.0	17.3	8.8	6.2	2.5	2.7	£29.01

Flexible Racks DR, ARL, SRS

22.0



Unit 14, Foxwood Industrial Park, Foxwood Road, Chesterfield, Derbyshire S41 9RN
Telephone +44(0)1246 268080 Fax +44(0)1246 260003